PMC6 High_End Laser Marking Controller

Advanced PCIe Bus Laser Marking Controller

Intro

PMC6 is a PCle interface high-performance laser marking controller. It supports digital scanner and very kinds of communication protocol. Provide sufficient I/O pins for variety application. The user could easily connect to automation and equipment, even for some kinds of laser that require IO. Build-in complete motor motion supports stepper and servo motor, and the card can control 4 axes simultaneously. Provide very kinds of cable for easy wiring frequently used equipment.



- Support common used brands of 16 \ 18 \ 20-bits high-resolution scanner.
- Support output up to 3 axes digital scanner signal * 2.
- Build-in DSP, marking computing does not hold CPU time.
- Galvo-motor-position updating rate at 10μs.
- FPK, PPK, R05 first pulse suppression.
- Two 16-bits analog control signals.
- Support 3-axis encoder inputs, for usage such as detection object position of fly-marking and XY table.
- PWM maximum output frequency is 10MHz, the minimum pulse width is 0.05μs.
- Support 4-axis motor control signals, the maximum output frequency is 10MHz.
- General 16 digital point outputs and inputs.
- Specific 16 laser control digital outputs.
- Support for Windows XP / 2000 / Vista / 7 / 8 / 10.

We reserve right to alter, edit or remove any function, in whole or in part, at our sole discretion.



Eastern Logic Inc. 興誠科技股份有限公司

Address:7F-4., No.75, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221, Taiwan

TEL: +886-2-2698296 FAX: +886-2-26983066 Email: service@elogic.com.tw